

**INTELLIGENT TFT SCREEN 40" SIZE 16:9 FORMAT**



**TFT SCREEN 40"**

**Specifications**

<b>Screen</b>	40", 16:9 format
<b>View angle</b>	170° Horizontal / Vertical
<b>Brightness</b>	500 cd/m2
<b>Contrast</b>	800:1
<b>Resolution</b>	1366 x 768 VGA; SVGA; XGA; S-XGA, U-XGA
<b>Connectors</b>	Ethernet RS-232 / RS-485 Power cable
<b>Dimensions (W x H x D)</b>	910 x 588 x 120 mm
<b>Power consumption</b>	260 W
<b>Weight</b>	35 Kg
<b>Power supply</b>	100-120V / 220-240V; 50/60Hz

**Internal Controller Characteristics**

- ★ 32 bit Intel or Intel compatible CPU
- ★ 128 Mb. SDRAM memory (Up to 512 Mb)
- ★ 20 GB IDE Hard Disk
- ★ IDE Controller Board
- ★ Socket for Solid State Memory
- ★ Ethernet 10/100 Base T Board with RJ-45 connector
- ★ Graphic Board with 8 MB RAM
- ★ Up to 3 RS-232 serial channels with DB9 connector
- ★ Up to 1 RS-485 serial channel with DB9 connector
- ★ Test Board capable of cyclically verifying the operation and physically restarting the system
- ★ Dual operation, both in remote and local modes, with , automatic mode detection and selection
- ★ Remote starting to overcome local failures of the storage media
- ★ All the elements and components selected and sized to support 24 over 24 hours operation
- ★ Main supply: 110 V / 240 V at 60 Hz. / 50 Hz.
- ★ Included power cable and monitor's control and video cables